UWS Academic Portal

Application of 3-D fluorescence

Zhu, Guocheng; Bian, Yongning; Hursthouse, Andrew; Wan, Peng; Szymannska, Katarzyna; Ma, Jiangya; Zhao, Zilong

Published in:
Journal of Fluorescence

DOI:
[10.1007/s10895-017-2146-7](https://doi.org/10.1007/s10895-017-2146-7)

E-pub ahead of print: 21/08/2017

Document Version
Peer reviewed version

[Link to publication on the UWS Academic Portal](#)

Citation for published version (APA):

Zhu, G., Bian, Y., Hursthouse, A., Wan, P., Szymannska, K., Ma, J., & Zhao, Z. (2017). Application of 3-D fluorescence: characterization of natural organic matter in natural water and water purification systems. *Journal of Fluorescence*, 27(6), 2069-2094. <https://doi.org/10.1007/s10895-017-2146-7>

General rights

Copyright and moral rights for the publications made accessible in the UWS Academic Portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

If you believe that this document breaches copyright please contact pure@uws.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.

Application of 3-D Fluorescence: Characterization of Natural Organic Matter in Natural Water and Water Purification Systems

Guocheng Zhu^{a,}, Yongning Bian^a, Andrew S Hursthouse^{a,b}, Peng Wan^c, Katarzyna Szymanska^{a,d}, Jiangya Ma^e, Xiaofeng Wang^c, Zilong Zhao^f*

a.Hunan Provincial Key Laboratory of Sale Gas Resource Utilization, Hunan University of Science and Technology, Xiangtan 411201, China

b.Institute of Biomedical & Environmental Health Research, School of Science & Sport, University of the West of Scotland, Paisley PA1 2BE, UK.

c.Department of Chemical Engineering, University of Missouri, Columbia, MO 65211, USA

d.Hydroklear Services Ltd, Paddockholm Industrial Estate, Riverside Place, Kilbirnie KA25 7PW, UK2

e.School of Civil Engineering and Architecture, Anhui University of Technology, Maanshan, Anhui 243002, China

f.School of Civil and Environmental Engineering, Harbin Institute of Technology Shenzhen, Graduate School, Shenzhen 518055, PR China

ABSTRACT

Natural organic matter (NOM) found in water sources is broadly defined as a mixture of polyfunctional organic molecules, characterized by its complex structure and paramount influence on water quality. Because the inevitable release of pollutants into aquatic environments due to an ineffective control of industrial and agricultural pollution, the interaction evaluations of NOM with heavy metals, nanoparticles, organic pollutants and other pollutants in the aquatic environment, are rapidly increased. The three-dimension (3-D) fluorescence has a potential to reveal the interaction mechanisms between NOM and pollutants as well as the source of NOM pollution. In water purification engineering system, the 3-D fluorescence can indicate the variations of NOM composition and gives an effective prediction of water quality as well as the underline water purification mechanisms. Inadequately treated NOM is a cause of precursors of disinfection byproducts (DBPs), posing a potential threat to human health. Effective control and measurement/evaluation of NOM have long been an important factor in prevention of water pollution. Overall, 3-D fluorescence allows for a rapid identification of organic components thus indicating possible sources of water pollution, mechanisms of pollutant interactions, and possible DBPs formed during conventional treatment of this water. This article reviews the 3-D fluorescence characteristics of NOM in natural water and typical water purification systems. The 3-D fluorescence was effective for indicateing the variabilities in NOM composition and chemistry thus providing a better understanding of NOM in natural water system and water engineering system.

KEYWORDS: 3-D fluorescence; indicator, natural organic matter; water purification

1. Introduction

Natural organic matter (NOM) is an essential component of aquatic environments. The chemical nature and composition of NOM, as well as its efficient removal are a major factor influencing the design and operation of water treatment plants. There is an urgent need for rapid assessment of quality of the water environment, meeting the needs of engineering system design. Three-dimension fluorescence (denoted as 3-D fluorescence) monitoring of NOM (denoted as 3-DFMM) using fluorescence excitation-emission matrix spectroscopy as a monitoring method has been widely used in water treatment processes (WTPs) to assess NOM chemical structure [1,2]. The NOM is a heterogeneous mixture of the organic molecules, originating from a range of sources [3]. Analyzing its chemical nature by the conventional methods, such as high performance size exclusion chromatography, Fourier transform infrared spectroscopy and nuclear magnetic resonance, is not cost-effective and is time consuming, which can be an issue for online monitoring at WTPs. However, using a 3-D fluorescence method to characterize NOM can provide a rapid, sensitive and simple approach with lower cost and simple sample preparation, and is potentially suitable for online monitoring of NOM [4-6]. In addition to the advantage of its low cost and simple operation, the 3-D fluorescence method has the advantage of separation of different fractions of NOM, which is beneficial to the understanding of their physico-chemical, and biological behaviors in the aquatic environments. For example, these fractions can often be identified and used to establish the source of organic pollution in the aquatic environments [7-9], and for quantifying NOM and associated products resulting from the reaction of NOM and disinfectants [10,11]. Because NOM originates from soil, plant and animal residues, and human activities, its chemical composition and molecular structure is complex and site-specific, thus its chemical properties vary not only from one site to another, but there are also seasonal changes in the same water source. The NOM has been known to produce a significant fluorescence signal while generating many kinds of characteristic peaks, which correspond to specific organic material sources. Among them, typical fluorescence peaks (e.g., corresponding to humic, fulvic and protein-like molecules) have been identified [12]. It is noteworthy that some NOM fractions correlate well with generic water quality parameters such as Total Organic Carbon (TOC). While TOC is considered as a parameter providing quantitative information about NOM content, it does not provide any information about its chemical characteristics. The 3-D fluorescence method may develop as a critical indicator for assessing the chemical nature of organic matter, with full potential to improve the efficiency of water treatment plants [13].

Organic compounds may be released into aquatic environment (and drinking water) by four major sources [14]: as natural organic matter (NOM), compounds originating from human activities, compounds formed by chemical reactions occurring during disinfection, and compounds formed or added during the treatment and transmission of water. Human activities are becoming increasingly important as a source of organic compounds and include organic chemicals from direct industrial, agricultural and municipal effluents. Both groundwater and surface water may be contaminated. The major sources of organic pollutants are industries utilizing large quantities of chemicals in the manufacturing process. Usually the organic compounds used in industry are synthetic organic compounds (SOCs) which are commonly found in water bodies at low concentrations. However, even at low concentrations they are of significant health concern. Common examples of SOCs found in water are: Benzene, Dichlorobenzenes, Methyl tert-butyl ether (MTBE), Toluene, Xylenes. Agricultural pesticides form an important class of organic pollutants and are widely dispersed in the environment. Some examples of herbicides typically of concern in WTPs : Atrazine, Cyanazine, Metribuzin. Despite the effectiveness of secondary treatment an increasing range of new organic compounds are detected in the effluents from treatment plants, these 'emerging organic compounds', originate from veterinary and human antibiotics, human drugs (prescription and nonprescription), and industrial and household wastewater products [14].

In order to improve water treatment efficiency and to investigate relevant mechanisms involved, fundamental research on colloidal particles and the distribution and transformation of organics in the aquatic environments is critical for explaining the characteristics and the corresponding variation in quality in water bodies [15]. The NOM found in aquatic systems contains a broad spectrum of organic compounds, such as humic substances, proteins, polysaccharides and other substances. The resulting profile is closely related to the design of WTPs as well as other factors such as the efficiency of water treatment and the formation of disinfection byproducts (DBPs) [16]. The observation of molecular fluorescence can be used to reveal their chemical characteristics. Analyzing the correlation between NOM fractions and the DBPs can be a useful tool in understanding the transformation of organic molecules in WTPs. In the last decade, 3-D fluorescence has been extensively studied in the assessment of WTPs, but there is lack of understanding of its fundamental properties of 3-D fluorescence response and the characterization of NOM.

Analyzing chemical nature of NOM via 3-D fluorescence offers an opportunity to improve the efficiency of monitoring and control of WTPs. This short review deals with the characteristics of the 3-D fluorescence of NOM and a specific environmental application of 3-DFMM in monitoring natural organic matter in WTPs

operations, which include the chemical/biological oxidation, coagulation-flocculation process and membrane/biological treatment process.

2. Analytical process and environmental influence

2.1. 3-D fluorescence spectra

The 3-D fluorescence spectra of NOM from a variety of sources, provides information about its chemical characteristics, which could be used for optimizing the performance of water treatment plants. The 3-D fluorescence is a three-dimensional contour plot, which can be obtained from a fixed scanning speed and varying excitation (EX) and emission wavelength (EM) at a fixed interval step. For analysis of data from 3-D fluorescence, although the collection of data is a simple operational process, there are some common interference resulting from the environmental conditions or instruments, which distort the actual fluorescence intensity. Therefore, spectrum correction is required to eliminate the interference. For instance, due to characteristics of instrumental components (e.g., excitation light source, monochromator and detector), the spectra are likely to be distorted. Using Rhodamine B as a quantum counter to correct spectroscopy intensity within the specific wavelength range of an excitation and emission wavelength can be a way of mitigating this interference [5]. The 3-D fluorescence include Rayleigh and Raman scattering (see Figure 1), which affects the analysis of 3-D fluorescence, especially modeling the 3-D fluorescence data. As seen from the Figure 1, larger Rayleigh scattering signal occurs, and the peak positions change with their excitation wavelength. These fluorescence data require some form of normalization because if they are modeled with parallel factor analysis (PARAFAC) to obtain fluorescence components, a new factor would be needed for each excitation wavelength [17]. Subtracting the background fluorescence of a pure water blank from emission spectrum of an observed sample is an important step in the pretreatment of 3-D fluorescence data in order to remove the majority of Raman scattering bands. The potential method for removing the interference of the scattering including both Rayleigh and Raman scattering can be completed using interpolation in the areas affected by the Rayleigh and Raman scatter, a method developed by Bahram, et al. [18].

Figure 1 3-D fluorescence of dissolved organic matter of artificial lake (Artificial lake was located on the Hunan University of Science and Technology campus, named as Yuhu Lake) (Self-scanned in the laboratory).

Figure 2 Fluorescence intensity inner filter effect on two components: fulvic acid-like and humic acid-like (the components were extracted from Aldrich humic acids) (Self-plotted in the laboratory).

In addition, during analysis of Dissolved Organic Matter (DOM) fluorescence, Dissolved Organic Carbon (DOC) is proportional to fluorescence intensities of several specific fluorescent fractions. However, with the increase of DOC concentration, the fluorescence intensities of components potentially deviates from a linear relationship (see Figure 2). This kind of optical phenomenon involves a significant decrease in emission quantum yield as a result of the absorption of excited and emitted radiation by a sample matrix, which is known as the “inner filter effect”. In water treatment engineering system, 3-DFMM analysis is susceptible to inner filter effect. Some samples such as surface water and sewage samples have to been pretreated if we want to obtain actual fluorescence intensity[19]. Therefore, the deviation of the fluorescence intensity during the analysis of NOM fluorescence components cannot be neglected. The inner filter effect

often has no significant influence for samples with low absorbance or concentration, thus there are two methods for reducing the influence of inner filter effect. The first method is to dilute the solution in order to decrease the absorbance (optical density) or concentration of a given sample. Absorbance can be used as an indicator for determination of the need for dilution. For example, Green, et al. [20] diluted the solution to a degree at optical density of 0.02 at 300 nm to avoid inner filtering of light within the sample in a 1 cm wide square quartz cell. Based on absorbance profile of sample, another classical model [21] can be used for the correction of modified fluorescence intensity, given as follows:

$$F_{\text{corr}} = F_{\text{obs}} \text{ antilog } ((OD_{\text{ex}} + OD_{\text{em}})/2) \quad (1)$$

where OD_{ex} and OD_{em} stand for the optical density of one sample at both excitation and emission wavelengths, respectively.

2.2. Typical NOM characteristics and fluorescence fractions

The NOM found in aquatic environments is composed of biological matter (carbohydrates, lipids, amino acids, nucleic acids) and the products of biotic and abiotic chemical reactions between NOM molecules or between NOM and inorganic constituents of water. The chemical properties of NOM vary significantly from one water body to another, where soil, climate and hydrologic conditions are different. Traditionally, NOM can be divided into three main groups based on their solubility in acid and alkali [14,22]: humic acid- soluble in dilute alkaline solutions but can be precipitated by acidification; molecular weights of HA are up to 200,000 g/mol, fulvic acid (FA) – remains in solution at low pH, molecular weights of FA are in the range of 200-1000 g/mol, humin – not soluble in water at any pH. NOM is much too complex to measure its individual components, so it is usually quantified by using bulk parameters such as Total Organic Carbon (TOC), Dissolved Organic Carbon (DOC), and UV254 absorbance. However, the above mentioned measurements do not provide any information about the nature of organic matter and its origins. For more specific purposes NOM can be also separated into fractions based on such properties as hydrophobicity, polarity or molecular weight [14].

Characteristics of different NOM fractions are presented in Table 1. It has been reported in the literature, that the main fraction of NOM present in surface waters contains humic substances, which are responsible for the color of natural waters. Presence of NOM in drinking water supplies is undesirable due to its reactivity with oxidants and disinfectants, which leads to a decrease in efficiency of these processes. Also, it may lead to formation of inorganic and organic disinfection by-products (DBPs), which cause health

concerns [23]. Another disadvantage of presence of NOM is the fact that the oxidized NOM is a nutrient for microbes in water distribution systems[24], so it promotes microbial growth in distribution systems[25].

Although there are many NOM fractions, the data provided by the 3-D fluorescence method can distinguish and be used to source multiple NOM fractions. Examples of several typical NOM fractions that are isolated from different aquatic environments, as well as their possible sources, are shown in Table 2.

Table 1 Characteristics of different NOM fractions.[26]

Fraction	Characteristics
Hydrophobic fraction	<p>Mostly representing hydrophobic acids: higher molecular weight (MW) humic acids, fulvic acid components and weak alkyl mono and dicarboxylic acids:</p> <ul style="list-style-type: none"> - complex, aromatic structure and high MW subunits; - anionic polyelectrolytes with acidic functional groups such as carboxylic acid, methoxyl, carbonyl and phenolic groups; <p>Few groups of neutral compounds with relatively low MW and a degree of condensed aromatic moieties: aromatic and aliphatic amines and amino acids.</p>
Intermediate or transphilic fraction	<p>Mostly relatively hydrophilic aliphatic acids.</p>
Hydrophilic fraction	<p>Mostly representing hydrophilic neutrals and some bases:</p> <ul style="list-style-type: none"> - aliphatic linear molecular structure; - lesser electron rich sites than in the hydrophobic fraction; - few groups of acids and bases with relatively low MW and a degree of condensed aromatic moieties; - lignin derived constituents with relatively low MW; - hydroxyl and sugar acids; - non-humic, aliphatic and low MW components, aromatic and aliphatic amines, amino acids; - polysaccharides and proteins;

Table 2 Characteristics of 3-D fluorescence fractions of NOM investigated in different water environments, and their potential source.

Aquatic environment	Dominant fluorescence	Excitation/Emission (Ex/Em) wavelength	Source	Reference
---------------------	-----------------------	--	--------	-----------

components		(nm)	
Algal suspensions through culture collection of algae	Protein-like materials	280/340 or 230/340	Blue-green algae (M. aeruginosa) : extracellular organic matter (EOM) and intracellular organic matter (IOM) and algal cell [27]
Impacted water along the Zhejiang coasts in China	Humic acid-like or protein-like materials	275/310 (tyrosine-like) and 275/340 (tryptophan-like) 342/442 (humic-like)	Submarine groundwater discharge, terrestrial inputs, land-based pollution, and local biological activities in combination [28]
Tributaries: Las Vegas Wash (LVW); upper Colorado River (UCR); lower Colorado River (LCR) (USA); Muddy River (MR); Virgin River (VR). They are located around Lake Mead reservoir between Arizona and Nevada in the USA.	Aromatic proteins, microbial by-products (for LVW, UCR and LCR); Fulvic acid-like, humic acid-like (for MR and VR)	220-250/280-332 (Aromatic proteins I), 220-250/ 332-380 (Aromatic proteins II), 250-470/280-380 (Microbial by-products) for LVW, UCR and LCR; 220-250/380-580 (Fulvic acid-like), 250-470/380-580 (humic acid-like) for MR and VR	Microbial activity or wastewater influence or autochthonous processes for LVW, UCR and LCR; limited microbial influence for MR and VR [29]
Nanming River in China	Fulvic acid-like substance (upstream); protein-like or tryptophan-like substance, and fulvic acid-like substances (downstream)	300-310/423-448 and 235-240/427-444 (fulvic acid-like, upstream); 275-280/337-351 and 225-230/340-347 (protein-like materials, downstream), 300-310/428-447 and 235-255/425-447 (fulvic -like materials, downstream)	Untreated sewerage effluents [30]
Kishon River in Israel	component I corresponding to humic-like matter; component II	345/438 (Component I); 280/364 (Component II)	Component I was linked to seawater tidal intrusion; Component II was associated with the location of major inputs of the industrial effluents [31]

		associated with biological productivity		
Planktonic bacteria Urban River Tame, Birmingham, UK	Amino acid-like materials (tryptophan and tyrosine-like substances)	(220,280)/320-37 (Tryptophan-like); approximately 220/around 240 (Tyrosine-like)	Bacterial activity (e.g., <i>Pseudomonas aeruginosa</i>)	[32]
Downstream samples on both the River Team and the Twizell Burn from Northeastern England, UK	Fulvic-like and tryptophan fluorescence (outfall, downstream);	276-281/340-370 (Tryptophan-like materials); 326-339/410-422 (Fulvic-like materials)	Sewage treatment works (STW) discharges	[33]

Although the NOM fluorescence fractions found in aquatic environments are different from the individual fluorescent compounds, their fluorescence are very similar. As the molecular structures of humic acid and fulvic acid are complex, they have no specific molecular formula, only the hypothetical structures as reviewed in Table 2. In previous research, International Humic Substances Society (IHSS) samples (Suwannee River humic acid standard used in this study) were applied as the standards for the humic and fulvic fractions [34]. Table 3 shows their similar fluorescence characteristics. In natural water system or water engineering system, these similar fluorescence fractions are called humic-like acid or fulvic-like acid components. The 3-D fluorescence spectra of the pure chemicals include tryptophan, tyrosine, and phenylalanin, which can be purchased and scanned in the laboratory are also presented in Table 3. Similar fluorescence characteristics are found for other components, such as protein-like materials. Overall, they are often used as standards to identify the category of DOM fractions. The fluorescence characteristics of typical Suwannee River NOM including humic acid and fulvic acid organic matter have been found in a range of water environments. A possible change to the positions of fluorescence peaks occurs due to the change of the aquatic environments.

In cases when an aquatic environment is affected by microorganisms (such as algae) the amount of abundant protein-like materials will be higher. The presence of this kind of organic matter has a significant impact on the overall composition of organic matter originating from this type of aquatic environment. The protein-like materials have similar characteristics to materials presented in Table 3, such as Tryptophan,

Tyrosine and Phenylalanine. At present, many identified fluorescence fractions (e.g., humic-like acid, fulvic-like acid, amino acid-like materials including proteins and peptides), share some similar compositions. Several kinds of commonly identified PARAFAC-based components have been widely distributed in aquatic environments [5,35]. Table 4 shows the typical PARAFAC-based components and their possible sources of water.

These fractions have become an important part of the chemical nature of NOM for specific water environments. Their chemical species derive from variety of sources, such as the humic-like acid and fulvic-like materials, potentially derived from decomposition of plants by biological and chemical processes [3], while the protein-like materials (mainly includes tryptophan-like and tyrosine-like) potentially originate from industrial and agricultural activity, or higher biological activity [32,27].

Table 3 Structure and 3-D fluorescence spectra of tryptophan, tyrosine, phenylalanine.

Name	Molecular formula	3-D fluorescence spectra
<p>Theoretical humic acid model [36]</p>		<p>Suwannee River humic acid standard [37]</p>
<p>Theoretical fulvic acid model [38]</p>		<p>Suwannee River fulvic acid standard [37]</p>

Tryptophan

Self-scanned in the laboratory

Tyrosine

Self-scanned in the laboratory

Phenylalanine

Self-scanned in the laboratory

Table 4 PARAFAC modeled fractions of DOM and possible sources of water.

Component	Excitation(nm)/Emission(nm)	Description
250/452	The component was terrestrially-derived component, which is common in various estuarine, marine and oceanic environments, such as river water[5], industrial wastewaters[40], drinking water [41], danish streams[42], freshwater ecosystem[43], natural water [44], water from trans-oceanic cruises in the Pacific and Atlantic oceans [45], water from Ise Bay, Japan[46], water from the South Atlantic bight[39].
Humic acid-like substances

250/420

Humic acid-like substances
[39]

The component was terrestrially-derived component, which is common in various estuarine, marine and oceanic environments, such as landfill leachate[47], industrial wastewaters[40], Danish estuary[7], ebinur lake watershed[48], water of typical agriculture, watershed of three Gorges reservoir areas[49], municipal solid waste leachate[50].

(250,310)/400

Marine humic substances[39]

The component was considered as marine humic substances resulting from microbial reprocessing. It was also identified as marine humic acid-like component or biological and microbial origin DOM [51], which has been found in several aquatic environments such as missouri river water[5], industrial wastewaters[40], landfill leachate[52], red wines[53], freshwater ecosystem [43], marine bacteria[54], coastal environments[55], the North Pacific Ocean, Bering, chukchi and Beaufort Seas [56], the South Atlantic Bight[39], Barataria Basin[57], coastal Canadian Arctic surface waters[58].

(270, 390)/508

Terrestrial organic matter[39]

The component was considered as terrestrial organic matter composed of high molecular weight and aromatic organic compounds. The component was also found in other aquatic environments such as synthetic DOM solution[59], Alpine lake catchments[60], Ballast water[61], water from the Baltic Sea [62].

270/332

Tyrosine-like substances [39]

The component was considered as tyrosine-like substance belonging to protein-like materials. The component was also found in other aquatic environments such as high-strength nitrogenous wastewater[63], lake water[64], submerged membrane bioreactor [65].

(250,290)/356

The component was considered as tryptophan-like substance belonging protein-like materials. The component was also found in other aquatic environments such as natural water [44], pools of a subtropical dryland river [66], lake water [64], freshwater ecosystems [43].

Tryptophan-like substances [39]

270/550

The component was considered as humic-like substances, correlated with anomeric, acetal and ketal carbon.

Humic-like substances [67]

2.3. Comparison of fluorescence fractions

Analysis of the chemical nature of NOM via 3-D fluorescence data includes both the qualitative and quantitative information. The qualitative analysis focuses on component identification. The identification process often involves search of the characteristic peaks over a wide range, followed by peak position matching with the previous findings or data from standard samples including both excitation wavelength and emission wavelength. An excitation and emission wavelength boundaries (lines) for different component regions can be used as references [68]. Subsequently, the type of component can be identified and classified. The analysis of 3-D fluorescence data containing additional information such as the relative content of a component can be interpreted by fluorescence intensity (FI), fluorescence index or other derived expressions. For instances, Bugden, et al. [69], used the slope ratio and the intensity ratios to interpret 3-D fluorescence data based on specific peak FI value in order to fingerprint oil and chemically dispersed oil in seawater. Chen, et al. [70] employed the fluorescence regional integration method for quantifying spectra for NOM in which the normalized fluorescence volume was used. This method was also present in the literature as a reference [71]. Whether it is qualitative or quantitative, using these fluorescence parameters is very effective. However, the main drawback of this method is that some fluorescence fractions could not be identified because of overlapping of the fluorescence signatures of individual compounds [5]. Therefore, 3-D fluorescence can be also coupled with PARAFAC to characterize NOM in natural water and give more

comprehensive results[2,72]. The PARAFAC model is effective for fractionation of the 3-D fluorescence data into the underlying fluorescence components based on an alternating least-squares algorithm, which extends the usefulness of this kind of spectroscopy [2]. The fractionations of 3-D fluorescence data into several independent fluorescent components by PARAFAC model is unique, which overcomes the problem of missing fractions [5]. In the practical engineering application, the variations in the intensity of fluorescence fractions can define the water quality. While the actual intensity of the fluorophore cannot be obtained through PARAFAC simulation, the fluorescence intensity at the maximum can be derived for each component so that the relative changes and the ratios between fluorescence components can illustrate the quantitative and qualitative difference between samples [39,17]. A complete PARAFAC simulation process is present in a previous literature as presented in Figure 3.

Figure 3 Fluorescence-based PARAFAC model analysis. [17]

In WTPs, a comparison between the PARAFAC-based components in the raw water and those in the treated water is needed. Only when the PARAFAC-based components have similar, high fluorescence characteristics including the components' contour plots and their excitation and emission loadings, their fluorescence intensity can be used to quantitatively analyze the degree of change, highlighting the differences in water quality before and after treatment. Similarity of these components can be quantitatively analyzed using Uncorrected Matrix Correlation(UMC)[73]. The UMC value between 0 and 1 is used to

measure the degree of spectral overlapping between two components. The 0 and 1 values for matrices indicate null and complete spectral overlapping, respectively. At present, the UMC have been used to compare the difference between the two components in nature water and water engineering system[74].

2.4. Background water matrix influence on the measurement

Various environmental factors have negative effects on analysis of 3-DFMM, including pH, metal ions, temperature, and photodegradation[75,3,13]. The pH and presence of metal ions effects have been widely studied, showing 3-D fluorescence to be applicable in a wider pH range of 2 to 12. The influence degree of pH in the 3-DFMM is dependent on specific fluorophores present in the water samples [3]. For example, Sorrentino et al. [76] indicated that the FI of two fluorescence fractions of river water increased with the increase of pH in the range of 2 to 10, with different responses to pH variation. For most natural water systems with the pH range normally from 5 to 9, less influence in 3-DFMM occurred [3]. Murphy, et al., [77] suggested that the pH influence in the spectral shape could be precluded because the pH and the treatment process stage were confounded variables; their results indicated that under such conditions PARAFAC model for fitting 3-D fluorescence data was successful.

In aquatic environments, various metal ions can be found, depending on the background water matrix and possible sources of pollution. The metal ions commonly present in water sources are: iron, aluminum, copper, mercury, chromium, cadmium, lead, nickel, zinc and vanadium, et al. [78]. Metal ions such as Cu^{2+} , Fe^{3+} , Hg^{2+} , Mg^{2+} and Cd^{2+} have been reported to quench the fluorescence of NOM, , et al., while the degree of fluorescence quenching was dependent on the fluorophore, metal ion concentration and speciation and pH conditions [13,3]. The modification effects of four kinds of metal ions, Hg, Cu, Fe and Al on the fluorescence of three fluorescence components of NOM in natural water system were compared [2]. It indicated that their effects on fluorescence modification of the identified components were not uniform and dependent on some specific factors. Hg, Cu and Fe had quenching effects on fluorescence of all components tested but Al had a quenching and enhancement effects on component 3, which had a greater quenching effect on component 2, followed by component 1. The metal ions concentration limitation that induces the quenching or enhancement of NOM was not clearly presented in this literature. Hudson, et al. [3], summarized the previous researches, which showed that the quenching effect of fulvic acids is obtained when using excess Cu, Fe and Al ions by varying their concentration as low as 0.1 mg/L. In the water treatment system, an accurate investigation of the effect of concentration of metal ions on fluorescence quenching of NOM still needs to study. In water treatment systems, the strict control of the output of the metal ions is important, which could reduce the influence of metal ions on the fluorescence analysis. In the

water treatment system, some researchers also reported no effects on wastewater fluorescence in the presence of metal ions[79,13]. With the wide use of nanomaterials, these materials will be inevitably released into the aquatic environments. The concerns on their long-term safety to human and inherent toxicity to aquatic organisms still remain. The nanomaterials treatment have become one of the issues of concern in WTPs [80]. During the transfer of nanomaterials in the aquatic environments, the NOM has been identified as an important carrier. The metal nanomaterials may result in a modification in their optical properties such as fluorescence quenching and enhancement. The fluorescence quenching or enhancement effects possibly indicate the interaction between NOM and metals. For example, the gold nanoparticles were coated with two different stabilizers, β -D-glucose and citrate, forming two products denoted as BG-GNPs and CT-GNPs[81] (see Figure 4). Their interactions with humic acid were expected as follows and the results of fluorescence quenching and enhancement by the nanoparticles were also shown in the figure.

Figure 4 Schematic of interactions between humic acid and BG-GNPs and CT-GNPs suggested by Vasantal, Pallem[81], and their fluorescence results of interactions. [81]

As seen from Figure 4, the interaction of humic acid with BG-GNPs resulted in a fluorescence quenching of humic acid but the CT-GNPs caused an enhancement of fluorescence intensity of humic acid[81]. The main reason for the enhancement was the overcoating effect of HA molecules on the citrate layer on GNPs[81]. In an observation tested in the lab, we can see a significant fluorescence quenching effect of DOM by the metal silver nanoparticles with time (see Figure 5). A near field electro dynamical environment of the metal nanoparticles would influence the fluorescence behaviors of humic acid[82,83]. The included electrolytes in model solution also influenced the fluorescence intensity of humic acid in which the calcium nitrate had a larger quenching effect[83]. Other interactions of nanoparticles and NOM, such as suwannee

River fulvic acid and iron oxide nanoparticles[84], which was demonstrated that different mechanisms of NP:SRFA binding with pH could be indicated by fluorescence quenching.

Figure 5 Fluorescence intensity quenching of Aldrich humic acids by silver nanoparticles with time at Ex (nm)/Em (nm) of 269/490 (tested in the laboratory).

Other factors such as photodegradation and temperature during 3-DFMM measurement may also affect the fluorescence of NOM [3]. In brief, in water treatment system, photodegradation can change NOM structure and character thus influencing the fluorescence intensity [85]; the degradation of NOM and the disinfection by UV exposure potentially impact NOM fluorescence analysis. Temperature has a significant impact on NOM fluorescence; however, using constant temperature may avoid any interference from thermal quenching during fluorescence analysis [3].

2.5. Environmental correlation

The aquatic NOM plays an important role in transmission or transformation of carbon, nitrogen and phosphorus, and of the toxic and hazardous substances, which poses a potential threat to human health. NOM structure has been extensively studied for many years while employing various methods to analyze the relationship between NOM and the water quality parameters. The organic matter has been known to interact with ultraviolet light, particular at 254 nm-wavelength adsorption (UV_{254}), which is more indicative of aromatic organic content. The aromatic organic materials are rich in carbon compounds, mainly originating from humic acid and fulvic acid materials, and the UV_{254} has been recognized to have a linear correlation with DOC, potential as a candidate for the latter to indicate water quality. Carbon and nitrogen are the primary elements of NOM, but NOM is most accounted of by carbon compounds. Therefore, the organic carbon compounds content is often calculated as the NOM concentration. 3-D fluorescence is able to yield

important information on the chemical nature of NOM [65], especially the aromatic organic materials. The aromatic carbon compounds can yield the carbonaceous DBPs, such as trihalomethanes (THMs), trichloroacetic acid and other (C-DBPs) [86]. Fulvic acid also has a significant impact on the formation of THMs, haloacetic acids, and aldehydes, while 2,3,5-tribromopyrrole can be produced from humic acid [87]. These imply that there should be a relationship between the fluorescence fractions and TOC or DBPs. Humic-like fluorescence was correlated well with DOC in marine DOM [88]. The squared correlation coefficient (R^2) between fluorescence intensity and DOC was up to 0.87. The cumulative normalized 3-D fluorescence volumes at some specific regions could correlate linearly with the dichloroacetic acid ($R^2=0.60$), chloroform ($R^2=0.42$), dichloroacetonitrile ($R^2=0.53$) [71]. F. Nakajima, et al. [89], suggested that the fluorescence intensity of DOM in a river system could present a good correlation with trihalomethane formation potential, and the fluorescence mainly originated from the THMs precursors. These demonstrate that the fluorescence fractions have a potential correlation with the yield of DBPs.

Besides aromatic carbon compounds, organic nitrogen compounds can also excite the fluorescence and generate the DBPs, and a significant correlation exists between the nitrogen compounds and the nitrogenous disinfection by-products (N-DBPs) as well as the organic nitrogen-related fluorescence fractions. The nitrogen-related fluorophores correlated with the protein and peptides materials are often present in three kinds of fluorescent amino acids, including tryptophan, tyrosine and phenylalanine [3]. The amino acids have been known to account for a significant portion of DON pool in natural lakes and streams and to generate N-DBPs [90]. Among them the tryptophan [91], tyrosine [92,93] and phenylalanine [94] have been reported to be the important components responsible for production of N-DBPs. In addition, for samples with higher concentrations, such as sewage, it showed a correlation between COD and protein-like fluorescence intensities [95]. The protein-like fluorescence intensity has been shown a possible tool for determining river water quality in earlier study [96], showing the statistically significant correlations of tryptophan-like fluorescence intensity at $Ex/Em=280nm/350nm$ with nitrate, phosphate, ammonia, and biochemical oxygen demand at $Ex/Em=220nm/350nm$ in River Tyne catchment (England), except for three polluted sites. The dissolved oxygen was then found not a good indicator of water quality. The effectiveness of the correlations was found to exist only when treated sewage, sewerage overflows or cross connections, or agricultural organic pollutants dominate water quality. In a landfill leachate solution, the leachate fluorescence intensity had a strong correlation with ammonia, TOC and biochemical oxygen demand [97]. The impacted river by leaking landfill leachate with high ammonia concentration affected the relationship,

where humic acid-like and fulvic acid-like materials were dominant fluorescent DOM[96]. When the sewerage sources of DOM are important, the use of tryptophan-like fluorescence intensity was suggested as a proxy for BOD, nitrate and phosphate[96]. Overall, it is likely to find a significant correlation between the fluorescence fractions and the corresponding N-DBPs; however, a warning needs to concern that cross contamination between water is likely to lead to a deterioration in fluorescence assessment of quantitative water quality parameters.

3. Application in water purification systems

3.1. Surface and groundwater treatment processes

The ultimate objective of water treatment processes is the removal of different pollutants from the water supply in order to ensure that the treated water quality meets with the appropriate standards. Depending on the water source, different constituents have to be removed during water treatment in order to meet specific water quality standards. As an example, different constituents, which can be found in ground and surface water, and which have to be removed in the water treatment train are presented in Table 5 [14]. To discuss in detail all the processes used for water treatment as beyond the scope of this review, so we will focus on chemical oxidation, coagulation/flocculation and biological/MBR processes.

Table 5 Typical constituents found in ground and surface water that may need to be removed in order to meet water quality objectives [14].

Class	Typical constituents found in:	
	Groundwater	Surface water
Floating and suspended materials	None;	Branches, leaves, algal compounds, soil particles;
Colloidal constituents	Microorganisms, trace organic and inorganic constituents;	Clay, silt, organic materials, pathogenic organisms, algae, other microorganisms;
Dissolved constituents	Iron and manganese, hardness ions, inorganic salts, trace organic compounds, radionuclides;	Organic compounds, tannic acids, hardness ions, inorganic salts, radionuclides;
Dissolved gases	Carbon dioxide, hydrogen sulfide;	-

3.2. Chemical Oxidation Processes

The WTPs use different treatment steps such as physical, chemical or physical-chemical, and biological processes. In these processes, the study of the fate and the structure of NOM is helpful in assessment of the environmental quality and the design of the water treatment engineering systems, thus it has received a wide attention. The 3-D fluorescence, assessment methodology allows frequent and informative monitoring of NOM [2], which favors the need of the increase in rapid assessment of WTPs.

Chemical oxidation and reduction methods are typically used in water treatment for the removal of specific inorganic and organic compounds from the treated water. Many different types of oxidation processes have been developed depending on their application, but there are three main types of oxidation processes used in water treatment that may be distinguished: Conventional oxidation processes; Oxidation processes at elevated temperatures and/or pressures; Advanced Oxidation Processes (AOPs); Chemical oxidation can be used as a pretreatment processes, as well as for the disinfection processes. The application of chemical oxidation as a pretreatment processes is usually needed when some chemically or biologically recalcitrant pollutants are present in the water to be treated. They are helpful in the improvement of the performance for the post-treatment processes. The performance of oxidation processes in removing contaminants can be enhanced using appropriate operation. The disinfection process is an essential operational unit used for killing bacteria and viruses using strong oxidants, such as chlorine, ozone and chlorine dioxide during chemical/biological oxidation processes. These oxidants have been found effective for those organic compounds as the precursors of the DBPs. The typical DBPs such as THMs, haloacetic acids (HAAs) and N-nitrosodimethylamine (NDMA) could form through the interactions of organic matters with the oxidants. Figure 6a shows the transformation of the organic matters including phenolates, olefins, and amines under oxidation conditions to DBPs such as HAAs and THMs, of the data was collected from the references [98]. The source of the organic matters can result from the NOM. The contained dimethylamine (DMA) or related compounds in surface and wastewaters could be transformed to NDMA (see Figure 6b). Other DBPs can also form through the interactions of NOM (such as algal organic matter) with the oxidants (see Figure 6c). The organic compounds are not completely mineralized, which are converted from large molecules into small molecules, and under different environmental conditions, it is feasible to produce organic 3-D fluorescence while the correlation between the fluorescence intensity and the DBPs potential is also expected.

Figure 6 Impact of chlorination, ozonation on DBPs formation [98](a), NDMA formation pathways [99](b), and the transformation of algal organic matter to DBPs [27](c).

During the oxidation process, 3-D fluorescence has been used to characterize the organic compounds and the formation of DBPs [95]. The reported changes in the 3-D fluorescence of NOM during water treatment processes could be explained by potential partial NOM reacting with the oxidants to form the DBPs [100-103]. The oxidants found in reducing fluorophores in all 3-D fluorescence regions played an important role [100]. The species in investigated regions were primarily identified as organic materials including humic-like, protein-like, and fulvic-like [100,103]. Among them the humic-like and protein-like had higher reactivity than the fulvic-like species [100]. Ozone and chlorine dioxide presented relatively higher reactivity of reacting with NOM fractions [103]. Better relationship between the specific DBPs formation potential and the fluorescence fractions was observed [104,100,101,105,102]. For example, the total THMs were found to be correlated strongly with the humic-like component [5]. NDMA has a moderate and significant correlation with the tryptophan-like component [105]; the production of the chloral hydrate and cyanogen chloride correlated well with the decrease in protein/tryptophan-like and humic-like fractions, respectively, during UV radiation in combination with chlorination/chloramination [104].

Although fluorescent DOM is only a subfraction of DOM and accurately assessing how much of the total DOM pool is represented by fluorescence is difficult, 3-D fluorescence is feasible for tracing the dynamics of DOM in natural ecosystems [106]. The changes in fluorescence fractions during the chemical/biodegradable oxidation also had a potential of assessing the formation potentials of DBPs.

In addition to the NOM, the release of organic matter were often produced from the metabolism of microorganisms, which include the release of organic matter by bacterial metabolic activity in activated sludge, and of the algal organic matter (AOM). These organic matters usually consist of extracellular organic matter (EOM) and intracellular organic matter (IOM) predominantly from the metabolic activity of algae or the cell decay [107,108]. The nature of this kind of organic matter is different from NOM [108], thus they are often investigated separately [27]. However, for their long-term release into the aquatic environments they have become an important components of NOM, significantly affecting the export of NOM. In addition, the presence of AOM, EOM and IOM in the drinking water system after the oxidation processes also have higher potential to generate the DBPs. With the frequent occurrence of algal blooms in drinking water reservoirs [27], it has posed a potential threat to water supply. Therefore, removal and characteristic analysis of AOM, EOM and IOM have been given a major consideration.

The observation of the nature of AOM indicates that the tryptophan-like (protein-like) rather than humic/fulvic acid-like dominates in the 3-D fluorescence of algae [108,109]. The peak positions found in the observation were centered at Ex/Em (nm/nm) wavelength pairs of 305/340 nm and 240/305 nm [108]. This implies that AOM is organic matter rich in nitrogen, with similar results previously described [27]. The 3-D fluorescence showed three fluorescence components (protein-like or organic nitrogen compounds, humic-like and fulvic-like that were accounted for by organic carbon compounds). Their fluorescence peaks corresponding to the organic nitrogen compounds was centered at the Ex/Em (nm/nm) wavelength pairs of 280/340, and 230/340, and those to the organic carbon compounds at 350/450 and 275/450 [27]. Higher portion of organic nitrogen compounds in AOM could generate more N-DBPs and haloaldehydes rather than the C-DBPs. EOM have relatively higher reactivity of generating DBPs except for trichloronitromethane in chlorination and chloramination than IOM as well as algal cells [27]. It also indicated that the chlorination of those algal cells including higher organic nitrogen content can generate more N-DBPs than the chlorination of NOM [110]. Therefore, the algal organic matter has become an important contribution to N-DBPs formation [111]. From above analysis, the 3-D fluorescence is able to provide a reliable information on analyzing chemical nature of AOM as well as the associated yields of DBPs. Because the N-DBPs have been considered more toxic than the most commonly regulated DBPs [112-114]. The correlation between N-DBPs formation potential and fluorescence fractions need to be studied further in order to effectively monitor and control the N-DBPs formation in WTPs.

In a more complex oxidation system including the introduction of photocatalysts in AOPs, 3-D fluorescence is also applied in a rapidly growing number of studies on catalytic and non-catalytic degradation of NOM, especially on the photodegradation of NOM [115-120]. For example, Phong, et al., [117] reported photocatalytic degradation of DOM using TiO_2 as a catalyst under various experimental settings. TiO_2 is a kind of various photocatalysts used widely in degradation of NOM (Figure 7a). It revealed that the DOM changes in fluorescence could be described by the combinations of four dissimilar components including one protein-like, two humic-like, and one terrestrial humic-like components, each degradation of which followed well the pseudo-first order model. The number of fluorescence components was determined based on split-half validation [121]. As a result, the protein-like component was preferentially removed by photocatalytic degradation probably due to its direct and preferable oxidation by hydroxyl radicals in solution. In addition to photocatalytic degradation, 3-D fluorescence was also applied in a non-catalytic photodegradation process for identifying components from NOM samples. For instance, Wada et al. [116] tested photoreactivity of the DOM from macroalgae using artificial sunlight and 3-D fluorescence analysis could showed generation of degradation products. First, 3-D fluorescence could indicated the fractions of macroalgae DOM (see Figure 7a) which shows two fluorescence peaks, and were identified as humic acid-like and tryptophan-like substances. However, fluorescence peaks of phenolic compounds were overlapped. Coupled with PARAFAC model, 3-D fluorescence extracted the phenolic fraction denoted as C3 (see Figure 7c). In the photo-degradation prcoess, C3 had a different variation from C1 and C2 with time under artificial sunlight. Furthermore, the decrease in C3 reflected the degradation of phenols. The increase in C2 implies that partial macroalgae DOM fractions had been transformed into lower molecular weight compounds, and subsequently accumulated as photo-degradation products. From the results of 3-D fluorescence analysis, photodecomposition has been found to be effective for phenolic compounds and the degradation products mostly contained the small molecules by low aromaticity. Overall, the 3-D fluorescence in investigating degradation of NOM have provided valuable information about the chemical composition and behaviors of DOM. These studies have profound implications for optimizing drinking water and wastewater treatments and for ensuring treated water quality and safety [122].

Figure 7 (a) Mechanism of TiO₂ photocatalysis process. [123]; (b) 3-D fluorescence of the macroalgal DOM which is collected on 0 h on the start of photodecomposition experiment, and the contour line means intensity of emission with an interval of 0.01 RU. Solid and dashed circles mean peaks 1 and 2, respectively [116]; and (c) components of macroalgal DOM was identified by PARAFAC model and the components are denoted as C1, C2 and C3.

3.3. Coagulation-flocculation Processes

Coagulation-flocculation process is widely used for the water and wastewater treatment. It is a very effective method for removal of colloids and suspended substances from the aquatic environments [124,125], along with other substances like organic matter and some metal ions. In addition to colloids and suspended substances, the coagulation-flocculation processes have been suggested to be a major treatment option for a better control of NOM and the associated DBPs [126]. To deeper understand the behaviors of the coagulation-flocculation for NOM and the associated DBPs, the characterization of NOM chemical nature is essential. A simple schematic of coagulation-flocculation for NOM and the introduction of 3-DFMM as shown in Figure 8.

Figure 8 Schematic diagram of coagulation-flocculation for NOM.

NOM in the aquatic environments often varies with the water environments, either in concentration or in species. Therefore, the chemical nature of NOM resulting from different environments is often different. Their removal is usually affected by their physical/chemical nature in the aquatic environments. In addition, they are also influenced by coagulant dosage and type, the mixing conditions as well as the ambient conditions [27,127]. The molecule size or molecule weights of NOM are important, of which the characterization is helpful in better understanding NOM removal behaviors.

The pH influence on the fluorescence intensity of organic matters has been considered[128]. With pH 4-7.5 and variation of residual aluminium, Gone et al.[129] plotted fluorescence intensity versus DOC for both raw and treated Agbo reservoir surface waters by coagulation-flocculation, it indicated a significant shift between representative water point for pH 4 and the other samples while with the optimum optimal dose of alum and the appropriate pH range of 4.5-7.5, the pH, residual aluminium and inner-filtering influences on fluorescence could be negligible. The significant high correlation between DOC removal and the fluorescence intensities of humic acid-like substances, fulvic acid-like substances and tryptophan-like also showed the 3-D fluorescence to evaluate the DOC removal to be feasible. Coagulation mechanisms could also be studied using fluorescence-quenching method [130]. The fluorescence quenching effect led to the residual humic acid TOC concentration to be higher than that measured by 3-D fluorescence. At both low and middle pH range, the major coagulation mechanism of coagulating humic acid by a polyferric sulfate was attributed to charge neutralization [130].

In an inorganic coagulation system, it had been demonstrated that the NOM fractions of raw water and the treated samples could be compared through a validation of UMC[72,2]. Missouri river water by the coagulation-flocculation process revealed three fluorescence fractions (humic acid-like, fulvic acid-like, and protein-like) [5]. The result showed that fluorescence fractions removals had a good correlation with DOC and DBPs reduction. The above study was mostly agree well with the previous findings [129]. The relatively straight forward removal of fluorescence components both indicated that it was effective for reducing humic acid-like and fulvic acid-like materials, while the protein-like fraction was relatively hard to treat [129,5]. The possible reason for the ease of component removal was largely attributed to the component nature such as molecular weight and solubility. Larger molecular weight compounds and the hydrophobic substances were easy to treat [131,132]. Further illustration describing 3-D fluorescence application in water treatment engineering system showed a long-term assessment of NOM in a multi-coagulant drinking water treatment scheme [72] in which two humic moieties (humic-like materials) and a protein-like structures similar to tryptophan were identified [72]. This research also indicated that humic-like materials were easy to treat, whereas the protein-like fraction was hard to reduce. Other further treatment technologies of NOM tend to use the combination model of 3-D fluorescence with other characterization methods. For example, Wassink et al. [133] used the 3-D fluorescence and the liquid chromatography–organic carbon detection to assess the removal of NOM and DBPs by enhanced coagulation, which could enable the quantitative detection of hydrophobic and hydrophilic DOC, thus it could provide better measurement of DBP precursors.

From the above findings, 3-D fluorescence is an effective tool for characterizing the NOM in coagulation-flocculation process in which the correlation is significant between some specific components and the water quality parameters such as DOC and DBPs. However, it was difficult to deal with organic nitrogen materials regardless of using aluminum and iron coagulants and composite coagulant. The fluorescence species, protein-like materials, including more organic nitrogen compounds, which were refractory to the coagulation-flocculation process [5,129]. This was not beneficial to the elimination of the N-DBPs. The protein-like materials would be considered as an indicator of the degree of reduction of N-DBPs. In addition to the coagulation-flocculation process, the adsorption and advanced oxidation were also found to have difficulties in reduction of organic nitrogen compounds [132]. In the aquatic environments, the organic nitrogen materials are less abundant, harder in detection and easy to create harmful nitrogen disinfection by-products, and are closely related to the design of WTPs as well as others such as water

treatment efficiency and the formation of N-DBPs. Therefore, the future rapid monitoring and control of the WTPs are necessary using 3-D fluorescence.

The precursors of N-DBPs are mainly composed of nitrogen organic compounds. For example, the precursors of halogen acetonitrile (HANs) formation are possibly free amino acids, nucleic acids, proteins, humic acid and small molecule amine reacting with chlorine and chloramines; the amino acids and humic acid are the precursors of chloropicrin in drinking water. Among them, the dissolved organic nitrogen (DON) can react with the disinfectant to generate N-DBPs [134,135]. The DON is a complex mixture consisting of less portion of DOM, which is composed of the materials such as amino acids, amides, amino sugars and peptides [92]. Some materials have fluorescence nature such as the typical amino acids including tryptophan, tyrosine and phenylalanine, which have been considered as indicative of proteins and peptides [3]. Therefore, the findings in the correlation between the fluorescence components and DON as well as the associated N-DBPs would be helpful in the understanding of formation of the N-DBPs. At present, the DON has posed a potential threat to human health and the removal of DON has been given more concern. Although 3-D fluorescence has been commonly used in WTPs, the fundamental research and its application involved in DON compounds and N-DBPs formation need to be investigated further.

Finally, because coagulation system often uses different coagulants according to water environment conditions, the 3-D fluorescence signal may be affected due to the fluorescence signal of external input or interference of external materials, especially the organic coagulants. The organic coagulants (e.g., polyacrylamide and polydimethyldiallylammonium chloride) can help inorganic coagulants to enhance their water treatment efficiency, accelerating floc aggregation, improving the settling rate, so it has become one of important methods to improve water purification in WTPs. However, these organic coagulants are a kind of macromolecular organic compounds which could excite a strong fluorescence signal (see Figure 9), possibly leading to a biased analysis in inherent fluorescence of NOM. With the rapid development of organic-inorganic composite coagulant, the organic coagulant influence in fluorescence of NOM has to be considered in the hope of providing technical support of eliminating interference of 3-D fluorescence.

Figure 9 3-D fluorescence of polyacrylamide (a), polydimethyldiallylammonium chloride (b). (polyacrylamide and polydimethyldiallylammonium chloride were the commercial cationic polymers (cationic degree=40%), which were purchased from China).

3.4. Biological/Membrane Bioreactor Treatment Processes

The performance of NOM removal in WTPs is largely improved by introducing the post-processes containing the biofilm process [136], activated sludge process [137], and membrane bioreactor treatment process [138]. Research on membrane fouling mechanisms via 3-D fluorescence has been developed rapidly in the recent years. For the short-term or long-term operation of the biofilm process and the activated sludge process, the types of biomasses resulting from these processes would have a major impact on the membrane performance, inevitably leading to membrane fouling. Membrane fouling refers to the process of membrane filtration in which the particles and the macromolecular species in the feed often interact with the membrane through deposition, reaction, precipitation, and/or microbiological process [139]. In the presence of the interaction, the particles and macromolecular solutes are possibly deposited or adhered to the membrane pores, or membrane surface (see Figure 10a). This would narrow or block the membrane pores, leading to the flux decline and needs for membrane cleaning and replacement.

Four classic filtration models can be used to analyze the flux decline of low-pressure membrane filtration in dead-end mode under constant pressure [140]. The schematic diagram of four filtration models is present in Figure 10b. According to the foulants distribution, the membrane fouling can be examined by analyzing

fluorescence fractions of those organic matters from the feed water, the membrane foulants, the membrane permeate, and others containing the sludge supernatant, extracellular polymeric substance in membrane filtration or bioreactor system [141,142].

Figure 10 (a) Schematic diagrams of membrane fouling overview and membrane fouling cross section view, (b) Schematic diagrams of four filtration models. [140].

Membrane bioreactor (MBR) was used in WTPs and the membrane fouling characteristics were investigated [143,144]. The fouling mechanism was dominated by the cake layer formation [141]. Considering the initial fouling nature of an aerobic submerged MBR [143], the dominant fluorescence foulants were considered to be protein-like substances [144,143]. Protein-like substances had been retained at the membrane surface [143]. Although their removal efficiency was greater, a significant increase of transmembrane pressure was recorded. For long-term operation of membrane bioreactor in a lab-scale MBR, the fluorescence aromatic and tryptophan proteins, the polysaccharides, lipids and fatty acids, originating from the sludge supernatant, were reported to be more easily contained by the fouling layer rather than humic-like and fulvic-like acids, in which aromatic proteins have higher fouling propensity than tryptophan proteins due to a higher hydrophobic nature [141]. Overall, protein-like fluorescence fractions have a significant contribution in membrane fouling processes. The pre-ozonation has a potential to reduce the protein-like substances resulting from both extracellular polymeric substance, which is helpful to reduce external and internal fouling [138]. In addition, ultrafiltration membrane pore size and surface hydrophobicity was found a significant influence in the transportation of protein-like substances but less importance for humic-like substances [140].

In addition to the significant contribution to membrane fouling in MBR systems, protein based materials were also the prominent components in the membrane fouling layer in the ultrafiltration (UF) system in which some humic-like materials, soluble microbial products and protein-like extracellular material could be removed efficiently while the fulvic-like matter was hard to reject [145]. In the ultrafiltration and nanofiltration membrane systems, another study suggested that the humic substances, protein-like and particulate/colloidal-like matter were the key membrane foulants[146-148]. However, for the submerged hollow fibre membrane bioreactor at a shorter hydraulic retention time, the humic-like and fulvic-like acid materials were the dominant foulants of membrane fouling formed on membrane surface, whereas at a longer hydraulic retention time, the foulants contained also a significant amount of biopolymers [149]. For different kinds of membranes used in water treatment system, their fluorescence fractions foulants may be varied (see Table 6), and the ambient conditions and molecular sizes as well as other factors would have a prominent influence on the membrane fouling.

Table 6 Identified membrane foulants in membrane treatment system using 3-D fluorescence.

Membrane process	Feed	3-D fluorescence of organic matter	Organic foulants	References
Microfiltration	Biologically treated secondary effluent	<p>(3-D Fluorescence of feed water (AP = aromatic protein, FA = fulvic acid-like, SMPs = soluble microbial products(e.g., proteins and polysaccharide-like materials), HA=humic acid-like))</p>	High molecular weight humic substances	[150]

Microfiltrration

Chitose River
water in Japan

Biopolymers and
protein-like
substances [151]

(3-D Fluorescence of chitose River water)

Nanofiltration

Synthetic
water samples
with NOM
derived from
allogenic
organic matter

Protein-like and
polysaccharide-
like substances [152]

(3-D Fluorescence of feed water)

Ultrafiltration

Chitose river
water in Japan

Polysaccharide-
like organic
matter [153]

(3-D Fluorescence of feed water)

Forward
Osmosis

Secondary
wastewater
effluent

Biopolymers and
protein-like
substances [154]

(3-D Fluorescence of feed water)

Reverse Osmosis Secondary
treated
municipal
wastewater

Protein-like
material [155]

(3-D Fluorescence of (a) RO feed water, and (b) extraction from fouled membrane sample. RO feed water included higher content of humic and fulvic acids, and protein but only modest amounts of protein-like material could be found in the extraction of fouled membrane samples.)

The biological WTPs are largely affected by the bacterial metabolic activity [156,157]. 3-D fluorescence is able to provide some specific information on those metabolites resulting from bacterial metabolic activity[158]. The monitoring of activated sludge in WTPs system is closely correlated with extracellular and intracellular substances due to their potential influence on bioreactor performance [156,159]. The extracellular substances are identified as being primarily composed of three fluorescence fractions including the protein-like substances, fulvic-like and humic-like materials among which the protein-like substances [157,156] reflect the changes in wastewater chemical oxygen demand [156]. In addition, it also showed that the intracellular fluorophores, proteins and nicotinamide adenine dinucleotide, had a better correlation with the bioreactor performance [156].

4. Summary

With the intensification of industry and agriculture, especially in developing countries, where urbanization is accelerating, the stress put on the environment is also increasing. The demand for water resources is also continually increasing in parallel to increase in pollution from industry and agriculture. Therefore, any enhancement of water quality monitoring and control, resulting in the improvement of water treatment

efficiency for WTPs is one of currently important topics. This article briefly reviews the specific application of 3-D fluorescence in monitoring NOM in WTPs. In this review, current research on the characterization of NOM by 3-D fluorescence, were reviewed. The 3-D fluorescence provides useful information to support better understanding of the performance of WTPs. The analysis of the source of pollution by NOM and online monitoring using the 3-D fluorescence in WTPs has been identified; the characterization of the transformation of NOM, especially in the DBPs formation, is a new challenge. Compared with the study of organic carbon compounds, research on the organic nitrogen compounds is relatively scarce. DON compounds are less abundant, harder in detection and responsible for creation of harmful nitrogen N-DBPs. In the WTPs, large molecular hydrophobic organic compounds are often easily removed, thus the reduction of C-DBPs is relatively effective. However, some small molecule organic hydrophilic compounds such as the protein, amino acid, amine compounds which are possibly correlated with the N-DBPs, are hard to deal with. The 3-D fluorescence offers the opportunity to provide more useful information revealing the mechanisms of their formation potential. These information provide support of man-made decision to prevent water from further pollution. The 3-D fluorescence monitoring of biological treatment systems has a potential to improve the online control of water quality. The 3-D fluorescence is relevant to membrane fouling analysis, but still needs to be further studied, especially in membrane fouling resulting from small molecular fractions of NOM. In order to ensure the safety of aquatic environment, the interactions between toxic and harmful substances and NOM is of considerable importance. The 3-D fluorescence monitoring of the optical properties of NOM in micro-scale is able to reveal their interaction behaviors with toxic and harmful substances, which is essential for better understanding of pollution process control.

Acknowledgments

This work is financially supported by National Natural Science Foundation of China. (No. 51408215 and 51408004) and by Innovate UK, through KTP009641 (KS). ASH acknowledges the support of Hunan Provincial Government and Hunan University of Science & Technology through High End Expert Scholarship.

References

1. Ahmad UK, Ulang Z, Yusop Z, Fong TL (2002) Fluorescence technique for the characterization of natural organic matter in river water. *Water Science & Technology* 46 (9):117-125

2. Ishii SK, Boyer TH (2012) Behavior of reoccurring PARAFAC components in fluorescent dissolved organic matter in natural and engineered systems: a critical review. *Environmental science & technology* 46 (4):2006-2017
3. Hudson N, Baker A, Reynolds D (2007) Fluorescence analysis of dissolved organic matter in natural, waste and polluted waters—a review. *River Research and Applications* 23 (6):631-649
4. Marhaba TF, Lippincott RL (2000) Application of fluorescence technique for rapid identification of DOM fractions in source waters. *Journal of Environmental Engineering* 126 (11):1039-1044
5. Zhu G, Yin J, Zhang P, Wang X, Fan G, Hua B, Ren B, Zheng H, Deng B (2014) DOM removal by flocculation process: Fluorescence excitation–emission matrix spectroscopy (EEMs) characterization. *Desalination* 346:38-45
6. Hofbauer DEW, Andrews SA (2004) Influence of UV irradiation and UV/hydrogen peroxide oxidation process on natural organic matter fluorescence characteristics. *Water Science & Technology Water Supply* 4 (4)
7. Stedmon CA, Markager S, Bro R (2003) Tracing dissolved organic matter in aquatic environments using a new approach to fluorescence spectroscopy. *Marine Chemistry* 82 (3):239-254
8. Huang L, Zhuo J, Guo W, Spencer RG, Zhang Z, Xu J (2013) Tracing organic matter removal in polluted coastal waters via floating bed phytoremediation. *Marine pollution bulletin* 71 (1):74-82
9. Hur J, Hwang S-J, Shin J-K (2008) Using synchronous fluorescence technique as a water quality monitoring tool for an urban river. *Water, air, and soil pollution* 191 (1-4):231-243
10. Fan Z, Gong S, Xu X, Zhang X, Zhang Y, Yu X (2014) Characterization, DBPs formation, and mutagenicity of different organic matter fractions in two source waters. *International journal of hygiene and environmental health* 217 (2):300-306
11. Baghoth SA, Dignum M, Grefte A, Kroesbergen J, Amy GL (2009) Characterization of NOM in a drinking water treatment process train with no disinfectant residual. *Water Science & Technology Water Supply* 9 (4)
12. Coble PG (1996) Characterization of marine and terrestrial DOM in seawater using excitation-emission matrix spectroscopy. *Marine chemistry* 51 (4):325-346
13. Henderson R, Baker A, Murphy K, Hambly A, Stuetz R, Khan S (2009) Fluorescence as a potential monitoring tool for recycled water systems: A review. *Water research* 43 (4):863-881

14. Crittenden J, Trussell, R. R., Hand, D. W., Howe, K. J., Tchobanoglous, G. (2005) *Water Treatment: Principles and Design*. vol Second Edition. John Wiley & Sons, Inc, New Jersey
15. Dongsheng Wang HL, Mingquan Yan, Jianfeng Yu, Hongxiao Tang (2006) Enhanced coagulation vs. optimized coagulation : A critical review. *Acta Scientiae Circum stantiae* 26 (4):544-551
16. Singer P (1999) Humic substances as precursors for potentially harmful disinfection by-products. *Water Science and Technology* 40 (9):25-30
17. Stedmon CA, Bro R (2008) Characterizing dissolved organic matter fluorescence with parallel factor analysis: a tutorial. *Limnology & Oceanography Methods* 6 (11):572-579
18. Bahram M, Bro R, Stedmon C, Afkhami A (2006) Handling of Rayleigh and Raman scatter for PARAFAC modeling of fluorescence data using interpolation. *Journal of Chemometrics* 20 (3-4):99-105
19. Hudson N, Baker A, Ward D, Reynolds DM, Brunsdon C, Carliellmarquet C, Browning S (2008) Can fluorescence spectrometry be used as a surrogate for the Biochemical Oxygen Demand (BOD) test in water quality assessment? An example from South West England. *Science of the Total Environment* 391 (1):149-158
20. Green SA, Blough NV (1994) Optical absorption and fluorescence properties of chromophoric dissolved organic matter in natural waters. *Limnology and Oceanography* 39 (8):1903-1916
21. Lakowicz JR (2006) *Principles of fluorescence spectroscopy*. Springer Science & Business Media, New York, USA
22. Zularisam A, Ismail A, Salim R (2006) Behaviours of natural organic matter in membrane filtration for surface water treatment—a review. *Desalination* 194 (1-3):211-231
23. Westerhoff P, Aiken G, Amy G, Debroux J (1999) Relationships between the structure of natural organic matter and its reactivity towards molecular ozone and hydroxyl radicals. *Water Research* 33 (10):2265-2276
24. Myllykangas T, Nissinen T, Rantakokko P, Martikainen P, Vartiainen T (2002) Molecular size fractions of treated aquatic humus. *Water research* 36 (12):3045-3053
25. Nissinen T, Miettinen I, Martikainen P, Vartiainen T (2001) Molecular size distribution of natural organic matter in raw and drinking waters. *Chemosphere* 45 (6):865-873
26. Metsämuuronen S, Sillanpää M, Bhatnagar A, Mänttari M (2014) Natural Organic Matter Removal from Drinking Water by Membrane Technology. *Separation & Purification Reviews* 43 (1):1-61
27. Fang J, Yang X, Ma J, Shang C, Zhao Q (2010) Characterization of algal organic matter and formation of DBPs from chlor (am) ination. *Water research* 44 (20):5897-5906

28. Gao L, Fan D, Li D, Cai J (2010) Fluorescence characteristics of chromophoric dissolved organic matter in shallow water along the Zhejiang coasts, southeast China. *Marine environmental research* 69 (3):187-197
29. Rosario-Ortiz FL, Snyder SA, Suffet IM (2007) Characterization of dissolved organic matter in drinking water sources impacted by multiple tributaries. *Water research* 41 (18):4115-4128
30. Mostofa KM, Wu F, Liu C-Q, Fang WL, Yuan J, Ying WL, Wen L, Yi M (2010) Characterization of Nanming River (southwestern China) sewerage-impacted pollution using an excitation-emission matrix and PARAFAC. *Limnology* 11 (3):217-231
31. Borisover M, Laor Y, Saadi I, Lado M, Bukhanovsky N (2011) Tracing organic footprints from industrial effluent discharge in recalcitrant riverine chromophoric dissolved organic matter. *Water, Air, & Soil Pollution* 222 (1-4):255-269
32. Elliott S, Lead J, Baker A (2006) Characterisation of the fluorescence from freshwater, planktonic bacteria. *Water Research* 40 (10):2075-2083
33. Baker A (2001) Fluorescence excitation-emission matrix characterization of some sewage-impacted rivers. *Environmental Science & Technology* 35 (5):948-953
34. Senesi N, Miano TM, Provenzano MR, Brunetti G (1989) Spectroscopic and compositional comparative characterization of I.H.S.S. reference and standard fulvic and humic acids of various origin. *Science of the Total Environment* 81-2 (1):143-156
35. Zhu G, Wang C, Dong X (2016) Fluorescence excitation-emission matrix spectroscopy analysis of landfill leachate DOM in coagulation-flocculation process. *Environmental Technology*:1-20
36. Stevenson FJ (1982) *Humus chemistry*. Wiley&Sons, NY.
37. Mobed JJ, † SLH, And JLA, McGown LB (1996) Fluorescence Characterization of IHSS Humic Substances: Total Luminescence Spectra with Absorbance Correction. *Environmental Science & Technology* 30 (10):3061-3065
38. Buffle J, Greter FL, Haerdi W (1977) Measurement of complexation properties of humic and fulvic acids in natural waters with lead and copper ion-selective electrodes. *Analytical Chemistry* 49 (2):216-222
39. Kowalczyk P DMJ, Young H, et al. (2009) Characterization of dissolved organic matter fluorescence in the South Atlantic Bight with use of PARAFAC model: Interannual variability. *Marine Chemistry* 113 (3):182-196

40. Liyang Yang DHH, Bo-Mi Lee, Jin Hur (2015) Characterizing treated wastewaters of different industries using clustered fluorescence EEM–PARAFAC and FT-IR spectroscopy: Implications for downstream impact and source identification. *Chemosphere* 127:222–228
41. Yulia Shutova AB, John Bridgeman, Rita K. Henderson (2014) Spectroscopic characterisation of dissolved organic matter changes in drinking water treatment: From PARAFAC analysis to online monitoring wavelengths. *Water Research* 54:159–169
42. M. Søndergaard CS, N. H. Borch (2004) Fate of terrigenous dissolved organic matter (DOM) in estuaries: Aggregation and bioavailability. *Ophelia* 57 (3):161-176
43. Jorge Nimptsch SW, Brian Kronvangb, Ricardo Gieseckea, Humberto E. Gonzáleza, Luciano Caputoa, Jörg Gelbrechte, Wolf von Tuemplingd, Daniel Graeberb (2014) Does filter type and pore size influence spectroscopic analysis of freshwater chromophoric DOM composition? *Limnologia - Ecology and Management of Inland Waters* 48:57-64
44. Phong D D HJ (2015) Insight into photocatalytic degradation of dissolved organic matter in UVA/TiO 2 systems revealed by fluorescence EEM-PARAFAC. *Water research* 87:119-126
45. Murphy K R SCA, Waite T D (2008) Distinguishing between terrestrial and autochthonous organic matter sources in marine environments using fluorescence spectroscopy. *Marine Chemistry* 108 (1):40-58
46. Yamashita Y JR, Maie N, et al. (2008) Assessing the dynamics of dissolved organic matter (DOM) in coastal environments by excitation emission matrix fluorescence and parallel factor analysis (EEM-PARAFAC). *Limnology and Oceanography* 53 (5):1900-1908
47. Lee S HJ (2016) Heterogeneous adsorption behavior of landfill leachate on granular activated carbon revealed by fluorescence excitation emission matrix (EEM)-parallel factor analysis (PARAFAC). *Chemosphere* 149:41-48
48. Wang X ZF, Ghulam A, et al. (2017) Evaluation and estimation of surface water quality in an arid region based on EEM-PARAFAC and 3D fluorescence spectral index: A case study of the Ebinur Lake Watershed, China. *CATENA* 155:62-74
49. Wang Q L JT, Zhao Z. (2016) Spectral characteristics of dissolved organic matter (DOM) in waters typical agricultural watershed of Three Gorges reservoir areas. *Environmental Science* 37 (6):2082-2092
50. Wu J ZH, Shao L M, et al. (2012) Fluorescent characteristics and metal binding properties of individual molecular weight fractions in municipal solid waste leachate. *Environmental pollution* 162 (63-71)
51. Gao Z GC (2017) Size distribution of absorbing and fluorescing DOM in Beaufort Sea, Canada Basin. *Deep Sea Research Part I: Oceanographic Research Papers* 121:30-37

52. Zhu G, Wang C, Dong X (2016) Fluorescence excitation–emission matrix spectroscopy analysis of landfill leachate DOM in coagulation–flocculation process. *Environmental Technology*:1-9
53. Diego Airado-Rodríguez TG-D, Isabel Durán-Merás and Jens Petter Wold (2009) Usefulness of Fluorescence Excitation–Emission Matrices in Combination with PARAFAC, as Fingerprints of Red Wines. *Journal of Agricultural & Food Chemistry* 5 (57):1711–1720
54. Shimotori K WK, Hama T. (2012) Fluorescence characteristics of humic-like fluorescent dissolved organic matter produced by various taxa of marine bacteria. *Aquatic Microbial Ecology* 65 (3):249-260
55. Yamashita Y JR, Maie N, et al. (2008) Assessing the dynamics of dissolved organic matter (DOM) in coastal environments by excitation emission matrix fluorescence and parallel factor analysis (EEM-PARAFAC). *Limnology and Oceanography* 53 (5):1900-1908
56. Dainard P G GC (2013) Distribution of PARAFAC modeled CDOM components in the North Pacific ocean, Bering, Chukchi and Beaufort seas. *Marine Chemistry* 157:216-223
57. Singh S DSEJ, Swenson E M. (2010) Chromophoric dissolved organic matter (CDOM) variability in Barataria Basin using excitation–emission matrix (EEM) fluorescence and parallel factor analysis (PARAFAC). *Science of the total environment* 408 (16):3211-3222
58. Walker S A ARMW, Stedmon C, et al. (2009) The use of PARAFAC modeling to trace terrestrial dissolved organic matter and fingerprint water masses in coastal Canadian Arctic surface waters. *Journal of Geophysical Research: Biogeosciences*, 114:1470-1478
59. Murphy KR, Stedmon CA, Waite TD, Ruiz GM (2008) Distinguishing between terrestrial and autochthonous organic matter sources in marine environments using fluorescence spectroscopy. *Marine Chemistry* 108 (1):40-58
60. Du Y ZY, Chen F, et al. (2016) Photochemical reactivities of dissolved organic matter (DOM) in a sub-alpine lake revealed by EEM-PARAFAC: An insight into the fate of allochthonous DOM in alpine lakes affected by climate change. *Science of The Total Environment* 568:216-225
61. Murphy K R RGM, Dunsmuir W T M, et al (2006) Optimized parameters for fluorescence-based verification of ballast water exchange by ships. *Environmental science & technology* 40 (7):2357-2362
62. Stedmon C A MS, Tranvik L, et al (2007) Photochemical production of ammonium and transformation of dissolved organic matter in the Baltic Sea. *Marine Chemistry* 104 (3):227-240

63. Maël Rusalleda BS-S, Bing-Jie Ni, Erik Arvin, M. Dolors Balaguer, Jesús Colprim, Barth F. Smets (2014) Spectrometric characterization of the effluent dissolved organic matter from an anammox reactor shows correlation between the EEM signature and anammox growth. *Chemosphere* 117:271-277
64. Kothawala DN, von Wachenfeldt, E., Koehler, B., Tranvik, L.J. (2012) Selective loss and preservation of lake water dissolved organic matter fluorescence during long-term dark incubations. *Science of the Total Environment* 433:238-246
65. Wang Z WZ, Tang S Characterization of dissolved organic matter in a submerged membrane bioreactor by using three-dimensional excitation and emission matrix fluorescence spectroscopy. *Water research* 43 (6):1533-1540
66. Fellman J B DS, Skrzypek G (2011) Hydrologic control of dissolved organic matter biogeochemistry in pools of a subtropical dryland river. *Water Resources Research* 47 (6):667-671
67. Nimptsch J, Woelfl S, Kronvang B, Giesecke R, González HE, Caputo L, Gelbrecht J, von Tuempling W, Graeber D (2014) Does filter type and pore size influence spectroscopic analysis of freshwater chromophoric DOM composition? *Limnologia-Ecology and Management of Inland Waters* 48:57-64
68. Chen W, Westerhoff P, Leenheer JA, Booksh K (2003) Fluorescence excitation– emission matrix regional integration to quantify spectra for dissolved organic matter. *Environmental science & technology* 37 (24):5701-5710
69. Bugden J, Yeung C, Kepkay P, Lee K (2008) Application of ultraviolet fluorometry and excitation– emission matrix spectroscopy (EEMS) to fingerprint oil and chemically dispersed oil in seawater. *Marine Pollution Bulletin* 56 (4):677-685
70. Chen W, Westerhoff P, Leenheer JA, Booksh K (2003) Fluorescence excitation-emission matrix regional integration to quantify spectra for dissolved organic matter. *Environmental science & technology* 37 (24):5701-5710
71. Yang X, Shang C, Lee W, Westerhoff P, Fan C (2008) Correlations between organic matter properties and DBP formation during chloramination. *Water research* 42 (8):2329-2339
72. Sanchez NP, Skeriotis AT, Miller CM (2014) A PARAFAC-based long-term assessment of DOM in a multi-coagulant drinking water treatment scheme. *Environmental science & technology* 48 (3):1582-1591
73. Burdick D, Xinm. TU (1989) THE WAVELENGTH COMPONENT VECTORGRAM: A TOOL FOR RESOLVING TWO-COMPONENT FLUORESCENT MIXTURES. *Journal of Chemometrics* (2):431-441

74. Sanchez NP, Skeriotis AT, Miller CM (2013) Assessment of dissolved organic matter fluorescence PARAFAC components before and after coagulation-filtration in a full scale water treatment plant. *Water Research* 47 (4):1679–1690
75. Schlautman MA, Morgan JJ (2002) Binding of a fluorescent hydrophobic organic probe by dissolved humic substances and organically-coated aluminum oxide surfaces. *Environmental Science & Technology* 27 (12):2523-2532
76. Patel-Sorrentino N, Mounier S, Benaim JY (2002) Excitation-emission fluorescence matrix to study pH influence on organic matter fluorescence in the Amazon basin rivers. *Water Research* 36 (10):2571-2581
77. Murphy KR, Hambly A, Singh S, Henderson RK, Baker A, Stuetz R, Khan SJ (2011) Organic matter fluorescence in municipal water recycling schemes: toward a unified PARAFAC model. *Environmental science & technology* 45 (7):2909-2916
78. Ahluwalia SS, Goyal D (2007) Microbial and plant derived biomass for removal of heavy metals from wastewater. *Bioresource Technology* 98 (12):2243-2257
79. Reynolds DM, Ahmad SR (1995) The effect of metal ions on the fluorescence of sewage wastewater. *Water Research* 29 (29):2214-2216
80. Benn TM, Westerhoff P (2008) Nanoparticle silver released into water from commercially available sock fabrics. *Environmental Science & Technology* 42 (11):4133-4139
81. Pallem V L SHA, Wells M J M. (2009) Evaluating aggregation of gold nanoparticles and humic substances using fluorescence spectroscopy. *Environmental science & technology* 43 (19): 7531-7535
82. Manoharan V, Ravindran A, Anjali CH (2014) Mechanistic Insights into Interaction of Humic Acid with Silver Nanoparticles. *Cell Biochemistry and Biophysics* 68 (1):127-131
83. Zhu G, Yin J (2016) Fluorescence Quenching of Humic Acid by Coated Metallic Silver Particles. *Journal of Fluorescence*:1-11
84. Manciulea A, Baker A, Lead JR (2009) A fluorescence quenching study of the interaction of Suwannee River fulvic acid with iron oxide nanoparticles. *Chemosphere* 76 (8):1023-1027
85. Guo Q, Zhang Z, Ma Z, Liang Y, Liu W (2014) Fluorescence characteristics of natural organic matter in water under sequential exposure to UV irradiation/chlor(am)ination. *Water Science & Technology Water Supply* 14 (1):22-30

86. Hong H, Huang F, Wang F, Ding L, Lin H, Liang Y (2013) Properties of sediment NOM collected from a drinking water reservoir in South China, and its association with THMs and HAAs formation. *Journal of Hydrology* 476:274-279
87. Richardson SD, Thruston AD, Rav-Acha C, Groisman L, Popilevsky I, Juraev O, Glezer V, McKague AB, Plewa MJ, Wagner ED (2003) Tribromopyrrole, brominated acids, and other disinfection byproducts produced by disinfection of drinking water rich in bromide. *Environmental science & technology* 37 (17):3782-3793
88. Wu F, Kothawala D, Evans R, Dillon P, Cai Y (2007) Relationships between DOC concentration, molecular size and fluorescence properties of DOM in a stream. *Applied Geochemistry* 22 (8):1659-1667
89. Nakajima F, Hanabusa M, Furumai H (2002) Excitation - Emission fluorescence spectra and trihalomethane formation potential in the Tama River, Japan. *Water Science & Technology Water Supply* 2 (5-6):481-486
90. Dotson A, Westerhoff P (2009) Occurrence and Removal of Amino Acids during Drinking Water Treatment. *Journal-American Water Works Association* 101 (9):101-115
91. Casbeer EM, Sharma VK, Zajickova Z, Dionysiou DD (2013) Kinetics and mechanism of oxidation of tryptophan by ferrate (VI). *Environmental science & technology* 47 (9):4572-4580
92. Chu W, Gao N, Krasner SW, Templeton MR, Yin D (2012) Formation of halogenated C-, N-DBPs from chlor (am) ination and UV irradiation of tyrosine in drinking water. *Environmental Pollution* 161:8-14
93. Chu W, Li D, Gao N, Templeton MR, Tan C, Gao Y (2014) The control of emerging haloacetamide DBP precursors with UV/persulfate treatment. *Water research*
94. Freuze I, Brosillon S, Herman D, Laplanche A, Démocrate C, Cavard J (2004) Odorous products of the chlorination of phenylalanine in water: formation, evolution, and quantification. *Environmental science & technology* 38 (15):4134-4139
95. Fabbicino M, Korshin GV (2004) Probing the mechanisms of NOM chlorination using fluorescence: Formation of disinfection by-products in Alento River water. 4 (4)
96. Baker A, Inverarity R (2004) Protein-like fluorescence intensity as a possible tool for determining river water quality. *Hydrological Processes* 18 (15):2927-2945
97. Baker A, Curry M (2004) Fluorescence of leachates from three contrasting landfills. *Water Research* 38 (10):2605-2613
98. De Vera GA, Keller J, Gernjak W, Weinberg H, Farré MJ (2016) Biodegradability of DBP precursors after drinking water ozonation. *Water Research* 106:550-561

99. Choi J, Valentine RL (2002) Formation of N-nitrosodimethylamine (NDMA) from reaction of monochloramine: a new disinfection by-product. *Water research* 36 (4):817-824
100. Liu C, Tang X, Kim J, Korshin GV (2015) Formation of aldehydes and carboxylic acids in ozonated surface water and wastewater: A clear relationship with fluorescence changes. *Chemosphere*
101. Liu C, Nanaboina V, Korshin G (2012) Spectroscopic study of the degradation of antibiotics and the generation of representative EfOM oxidation products in ozonated wastewater. *Chemosphere* 86 (8):774-782
102. Korak JA, Wert EC, Rosario-Ortiz FL (2015) Evaluating fluorescence spectroscopy as a tool to characterize cyanobacteria intracellular organic matter upon simulated release and oxidation in natural water. *Water research* 68:432-443
103. Świetlik J, Sikorska E (2004) Application of fluorescence spectroscopy in the studies of natural organic matter fractions reactivity with chlorine dioxide and ozone. *Water Research* 38 (17):3791-3799
104. Lyon BA, Cory RM, Weinberg HS (2014) Changes in dissolved organic matter fluorescence and disinfection byproduct formation from UV and subsequent chlorination/chloramination. *Journal of hazardous materials* 264:411-419
105. Yang L, Kim D, Uzun H, Karanfil T, Hur J (2015) Assessing trihalomethanes (THMs) and N-nitrosodimethylamine (NDMA) formation potentials in drinking water treatment plants using fluorescence spectroscopy and parallel factor analysis. *Chemosphere* 121:84-91
106. Stedmon CA, Markager S (2005) Resolving the variability in dissolved organic matter fluorescence in a temperate estuary and its catchment using PARAFAC analysis. *Limnology and Oceanography* 50 (2):686-697
107. Ma M, Liu R, Liu H, Qu J, Jefferson W (2012) Effects and mechanisms of pre-chlorination on *Microcystis aeruginosa* removal by alum coagulation: Significance of the released intracellular organic matter. *Separation and Purification Technology* 86:19-25
108. Henderson RK, Baker A, Parsons SA, Jefferson B (2008) Characterisation of algogenic organic matter extracted from cyanobacteria, green algae and diatoms. *Water research* 42 (13):3435-3445
109. Qu F, Liang H, He J, Ma J, Wang Z, Yu H, Li G (2012) Characterization of dissolved extracellular organic matter (dEOM) and bound extracellular organic matter (bEOM) of *Microcystis aeruginosa* and their impacts on UF membrane fouling. *Water research* 46 (9):2881-2890
110. Yang X, Guo W, Shen Q (2011) Formation of disinfection byproducts from chlor (am) ination of algal organic matter. *Journal of hazardous materials* 197:378-388

111. Shah AD, Mitch WA (2011) Halonitroalkanes, halonitriles, haloamides, and N-nitrosamines: a critical review of nitrogenous disinfection byproduct formation pathways. *Environmental science & technology* 46 (1):119-131
112. Kristiana I, Tan J, Joll CA, Heitz A, Von Gunten U, Charrois JW (2013) Formation of N-nitrosamines from chlorination and chloramination of molecular weight fractions of natural organic matter. *Water research* 47 (2):535-546
113. Padhye LP, Hertzberg B, Yushin G, Huang C-H (2011) N-nitrosamines formation from secondary amines by nitrogen fixation on the surface of activated carbon. *Environmental science & technology* 45 (19):8368-8376
114. Richardson SD, Postigo C (2012) Drinking water disinfection by-products. In: *Emerging organic contaminants and human health*. Springer, pp 93-137
115. Chen M, Jaffé R (2014) Photo-and bio-reactivity patterns of dissolved organic matter from biomass and soil leachates and surface waters in a subtropical wetland. *Water research* 61:181-190
116. Wada S, Omori Y, Kayamyo Y, Tashiro Y, Hama T (2015) Photoreactivity of dissolved organic matter from macroalgae. *Regional Studies in Marine Science* 2:12-18
117. Phong DD, Hur J (2015) Insight into photocatalytic degradation of dissolved organic matter in UVA/TiO₂ systems revealed by fluorescence EEM-PARAFAC. *Water research* 87:119-126
118. Du Y, Zhang Y, Chen F, Chang Y, Liu Z (2016) Photochemical reactivities of dissolved organic matter (DOM) in a sub-alpine lake revealed by EEM-PARAFAC: An insight into the fate of allochthonous DOM in alpine lakes affected by climate change. *Science of The Total Environment* 568:216-225
119. Phong DD, Hur J (2016) Non-catalytic and catalytic degradation of effluent dissolved organic matter under UVA-and UVC-irradiation tracked by advanced spectroscopic tools. *Water Research* 105:199-208
120. Chen M, Jaffé R (2016) Quantitative assessment of photo-and bio-reactivity of chromophoric and fluorescent dissolved organic matter from biomass and soil leachates and from surface waters in a subtropical wetland. *Biogeochemistry* 129 (3):273-289
121. Stedmon CA, Bro R (2008) Characterizing dissolved organic matter fluorescence with parallel factor analysis: a tutorial. *Limnology and Oceanography: Methods* 6 (11):572-579
122. Yang L, Hur J, Zhuang W (2015) Occurrence and behaviors of fluorescence EEM-PARAFAC components in drinking water and wastewater treatment systems and their applications: a review. *Environmental Science and Pollution Research* 22 (9):6500-6510

123. Samsudin EM, Sze NG, Ta YW, Tan TL, Hamid SBA, Joon CJ (2015) Evaluation on the photocatalytic degradation activity of Reactive Blue 4 using pure anatase nano-TiO₂. *Sains Malaysiana* 44 (7):1011-1019
124. Zhu G, Zheng H, Zhang Z, Tshukudu T, Zhang P, Xiang X (2011) Characterization and coagulation–flocculation behavior of polymeric aluminum ferric sulfate (PAFS). *Chemical Engineering Journal* 178:50-59
125. Zhu G, Zheng H, Chen W, Fan W, Zhang P, Tshukudu T (2012) Preparation of a composite coagulant: Polymeric aluminum ferric sulfate (PAFS) for wastewater treatment. *Desalination* 285:315-323
126. Matilainen A, Vepsäläinen M, Sillanpää M (2010) Natural organic matter removal by coagulation during drinking water treatment: A review. *Advances in Colloid and Interface Science* 159 (2):189-197
127. Zheng H, Zhu G, Jiang S, Tshukudu T, Xiang X, Zhang P, He Q (2011) Investigations of coagulation–flocculation process by performance optimization, model prediction and fractal structure of flocs. *Desalination* 269 (1):148-156
128. Antunes MCG, Pereira CC, Da Silva JCE (2007) MCR of the quenching of the EEM of fluorescence of dissolved organic matter by metal ions. *Analytica chimica acta* 595 (1):9-18
129. Gone DL, Seidel J-L, Batiot C, Bamory K, Ligban R, Biemi J (2009) Using fluorescence spectroscopy EEM to evaluate the efficiency of organic matter removal during coagulation–flocculation of a tropical surface water (Agbo reservoir). *Journal of hazardous materials* 172 (2):693-699
130. Cheng WP, Chi FH (2002) A study of coagulation mechanisms of polyferric sulfate reacting with humic acid using a fluorescence-quenching method. *Water Research* 36 (18):4583-4591
131. Matilainen A, Lindqvist N, Korhonen S, Tuhkanen T (2002) Removal of NOM in the different stages of the water treatment process. *Environment International* 28 (6):457-465
132. Bagastyo AY, Keller J, Poussade Y, Batstone DJ (2011) Characterisation and removal of recalcitrants in reverse osmosis concentrates from water reclamation plants. *Water research* 45 (7):2415-2427
133. Wassink JK, Andrews RC, Peiris RH, Legge RL (2011) Evaluation of fluorescence excitation–emission and LC-OCD as methods of detecting removal of NOM and DBP precursors by enhanced coagulation. *Water Science & Technology Water Supply* 11 (5):621-630
134. Bond T, Huang J, Templeton MR, Graham N (2011) Occurrence and control of nitrogenous disinfection by-products in drinking water—a review. *Water research* 45 (15):4341-4354

135. Lee W, Westerhoff P, Croué J-P (2007) Dissolved organic nitrogen as a precursor for chloroform, dichloroacetonitrile, N-nitrosodimethylamine, and trichloronitromethane. *Environmental science & technology* 41 (15):5485-5490
136. Fan L, Nguyen T, Roddick FA (2011) Characterisation of the impact of coagulation and anaerobic biotreatment on the removal of chromophores from molasses wastewater. *water research* 45 (13):3933-3940
137. Karthik M, Dafale N, Pathe P, Nandy T (2008) Biodegradability enhancement of purified terephthalic acid wastewater by coagulation–flocculation process as pretreatment. *Journal of hazardous materials* 154 (1):721-730
138. Liu T, Chen Z-l, Yu W-z, You S-j (2011) Characterization of organic membrane foulants in a submerged membrane bioreactor with pre-ozonation using three-dimensional excitation–emission matrix fluorescence spectroscopy. *Water research* 45 (5):2111-2121
139. Shi X, Field R, Hankins N (2011) Review of fouling by mixed feeds in membrane filtration applied to water purification. *Desalination and Water Treatment* 35 (1-3):68-81. doi:10/5004/dwt.2011.3131
140. Qu F, Liang H, Zhou J, Nan J, Shao S, Zhang J, Li G (2014) Ultrafiltration membrane fouling caused by extracellular organic matter (EOM) from *Microcystis aeruginosa*: effects of membrane pore size and surface hydrophobicity. *Journal of Membrane Science* 449:58-66
141. Meng F, Zhou Z, Ni B-J, Zheng X, Huang G, Jia X, Li S, Xiong Y, Kraume M (2011) Characterization of the size-fractionated biomacromolecules: Tracking their role and fate in a membrane bioreactor. *Water research* 45 (15):4661-4671
142. Wang Z, Wu Z, Tang S (2009) Extracellular polymeric substances (EPS) properties and their effects on membrane fouling in a submerged membrane bioreactor. *Water research* 43 (9):2504-2512
143. Ng TCA, Ng HY (2010) Characterisation of initial fouling in aerobic submerged membrane bioreactors in relation to physico-chemical characteristics under different flux conditions. *Water research* 44 (7):2336-2348
144. Wang Z, Wu Z, Tang S (2009) Characterization of dissolved organic matter in a submerged membrane bioreactor by using three-dimensional excitation and emission matrix fluorescence spectroscopy. *Water research* 43 (6):1533-1540
145. Nguyen T, Fan L, Roddick F, Harris J (2009) A comparative study of microfiltration and ultrafiltration of activated sludge-lagoon effluent. *Desalination* 236 (1):208-215

146. Peiris BRH, Hallé C, Legge RL, Peldszus S, Jekel M, Huck PM, Haberkamp J, Moresoli C, Budman H, Amy G (2008) Assessing nanofiltration fouling in drinking water treatment using fluorescence fingerprinting and LC-OCD analyses. *Water Science & Technology Water Supply* 8 (4)
147. Her N, Amy G, Yoon J, Song M (2003) Novel methods for characterizing algogenic organic matter and associated nanofiltration membrane fouling. *Water Science & Technology Water Supply* 3 (5-6):165-174
148. Peiris RH, Hallé C, Budman H, Moresoli C, Peldszus S, Huck PM, Legge RL (2010) Identifying fouling events in a membrane-based drinking water treatment process using principal component analysis of fluorescence excitation-emission matrices. *Water Research* 44 (1):185-194
149. Hong S, Aryal R, Vigneswaran S, Johir M, Kandasamy J (2012) Influence of hydraulic retention time on the nature of foulant organics in a high rate membrane bioreactor. *Desalination* 287:116-122
150. Pramanik BK, Roddick FA, Fan L (2016) Long-term operation of biological activated carbon pre-treatment for microfiltration of secondary effluent: Correlation between the organic foulants and fouling potential. *Water research* 90:405-414
151. Kimura K, Tanaka K, Watanabe Y (2014) Microfiltration of different surface waters with/without coagulation: clear correlations between membrane fouling and hydrophilic biopolymers. *Water research* 49:434-443
152. Her N, Amy G, Park H-R, Song M (2004) Characterizing algogenic organic matter (AOM) and evaluating associated NF membrane fouling. *Water research* 38 (6):1427-1438
153. Kimura K, Hane Y, Watanabe Y, Amy G, Ohkuma N (2004) Irreversible membrane fouling during ultrafiltration of surface water. *Water research* 38 (14):3431-3441
154. Linares RV, Yangali-Quintanilla V, Li Z, Amy G (2012) NOM and TEP fouling of a forward osmosis (FO) membrane: foulant identification and cleaning. *Journal of membrane science* 421:217-224
155. Ho JS, Sim LN, Webster RD, Viswanath B, Coster HG, Fane AG (2017) Monitoring fouling behavior of reverse osmosis membranes using electrical impedance spectroscopy: A field trial study. *Desalination* 407:75-84
156. Li W-H, Sheng G-P, Liu X-W, Yu H-Q (2008) Characterizing the extracellular and intracellular fluorescent products of activated sludge in a sequencing batch reactor. *Water Research* 42 (12):3173-3181
157. Ni B-J, Fang F, Xie W-M, Sun M, Sheng G-P, Li W-H, Yu H-Q (2009) Characterization of extracellular polymeric substances produced by mixed microorganisms in activated sludge with gel-permeating

chromatography, excitation–emission matrix fluorescence spectroscopy measurement and kinetic modeling.

Water research 43 (5):1350-1358

158. Esparza-Soto M, Westerhoff PK (2001) Fluorescence spectroscopy and molecular weight distribution of extracellular polymers from full-scale activated sludge biomass. Water Science & Technology 43 (6):87-95

159. Sheng G-P, Yu H-Q (2006) Characterization of extracellular polymeric substances of aerobic and anaerobic sludge using three-dimensional excitation and emission matrix fluorescence spectroscopy. Water Research 40 (6):1233-1239